



**Stock #: 245678**

**Technical Specification**

**and**

**Scope of Supply**

**mtu 6R0120 DS200  
DG06RM120A3N**

**Customer:** INDEL Power Group LLC

19.05.2023



A Rolls-Royce  
solution

## I. System Description

Product type	DG06RM120A3N
Application Group	mtu 6R0120 DS200
	3D - Emergency Standby power, IFN

### Power as per MTU Sales Program

Power per genset (ISO 8528)	200	kWel
Engine speed	1.800	rpm
Intake air temperature	25	°C
Coolant temperature	0	°C
Altitude	100	m

### On-site Power

Power per genset (ISO 8528)	200	kWel
Engine speed	1.800	rpm
Intake air temperature	25	°C
Coolant temperature	0	°C
Altitude	100	m

### Requirements

Frequency	60 Hz
Generator voltage	208 V
EngineType	6R926G80S
Generator model	Marathon




A Rolls-Royce  
solution

## II. Selection Criteria for the Scope of Supply

<b>Criteria</b>	<b>Selection</b>	<b>for Product No.</b>
Application	Emergency Standby (3D)	1,
Frequency	60 Hz	1,
Generator Voltage	208 V	1,
Phase	3 Phase	1,
Unit Specification	UL2200	1,
IBC Seismic Certification	Without IBC	1,
HCAI Certification	Without HCAI	1,
Engine Model	6R 7.2L OM926LA (12volts)	1,
Exhaust Emissions (EPA)	EPA "Nonroad" T. 3 Stationary (40 CFR 60)	1,
Radiator Design Temperature	50°C	1,
Temp Rise	105°	1,
Power Output	200 kW	1,
Full Load Amps	693	1,
Generator Frame and Wire Qty	431/6208 (12 Wire)	1,
Generator Wire Configuration	Wye	1,
OPU/HSD	Level 3 - Maximum Sound Attenuation	1,
Fuel Tank	With Tank	1,
Control panel	With Control Panel	1,
Circuit Breaker Options	Single Circuit Breaker	1,
Breaker Wire Color Scheme	Standard Breaker Wire Color Scheme	1,
Paralleling	No Paralleling Operation	1,
Acceptance testing	Factory acceptance	1,
Country of Operation	USA/Canada	1,
Emission cert. authority	18 US EPA Agency	1,


### III. Scope of Supply

	valid for product no.
<b>1 SYSTEM CONFIGURATION</b>	1,
<b>1.1 System Description</b>	1,
Model: DG06RM120A3N	1,
<b>1.2 Cooling Package</b>	1,
50 Deg C Cooling System	1,
• Closed loop, liquid cooled, with radiator factory mounted on engine-generator set mounting frame and integral engine-driven coolant pump	
<b>1.3 Circuit Breaker</b>	1, 1,



**Top View**      **Right Side**      CB Position 1/CB Position 2  
**Left Side**      Controls/CB Position 3

\* For technical data refer to the circuit breaker enclosure data sheets located on the Business Portal



**Top View**      **Right Side**      CB Position 1  
**Left Side**      Controls

\* For technical data refer to the circuit breaker enclosure data sheets located on the Business Portal

Single Circuit Breaker	1,
<b>Circuit Breaker Position 1:</b>	1,



A Rolls-Royce  
solution

valid for  
product no.  
1,  
800 Amp 600 Volt 3 Pole 100% LSI CB SQ-D PGL36080CU33A

**Circuit Breaker #1 Accessories:** 1,

Standard Breaker Wire Scheme: 1,

- Phase 1 (A) is Black label "L1"
- Phase 2 (B) is Red label "L2"
- Phase 3 (C) is Blue label "L3"
- Neutral is White label "NEU"

**Circuit Breaker Position 1:** 1,

LSI Breaker Trip: 1,

- LSI breakers provide protection from long time overload, short time overload and instantaneous short circuit events. Specific overload current values and time delays vary with breaker type and trip unit.

**1.4 Starting Aids** 1,

Starting Battery (Group 31), Cables & Battery Rack 1,

- Battery Rack mounted and installed
- Battery Group 31 Starting Battery filled with acid
- Qty 1

Battery Charger: MicroGenius 10A 1,

- 180W
- 10 Amp
- 12V
- NFPA 110

Battery Charger Mounted & AC/DC Wired 1,

**\*Note\*** - This option will be factory-wired to the distribution panel (if selected) 1,

With Coolant Preheating 1,

Coolant Preheater 1,

- -20 Deg F Coolant Preheater (120V 1PH - 1500W)
- Model: TPS151GT10-005



A Rolls-Royce  
solution

valid for  
product no.

- Qty 1

Coolant Preheater Mounted & AC Wired	1,
<b>1.5 Genset Enclosure</b>	1,
OM900 Level 3 Enclosure	1,
• Level 2 enclosure with air exhaust scoop.	
• UL 94 HF-1 compliant, 1.5" thick sound attenuated foam insulation installed in scoop.	
Weather Proof Enclosure - Aluminum	1,
195mph Wind Rated	1,
Sound Attenuation Kit	1,
Sound Attenuation Kit	1,
Exhaust Scoop - Aluminum	1,
<b>1.6 Vibration Isolation</b>	1,
SUA63015 Pad Isolators	1,
• ¼ inch thick elastomeric pad in rectangular shape placed under the base frame at each of the pre-drilled isolator mounting holes	
<b>2 ENGINE CONFIGURATION</b>	1,
<b>2.1 Engine System</b>	1,
6R 7.2L OM926LA Charged Air Cooling	1,
<b>Note Emission Compliance:</b>	1,
The engines and/or systems, may only be certified to comply with the required country or region specific emission regulations. Where applicable, the engines and/or systems are only certified to those specific emission regulations/standards which are clearly stated in the respective RRPS/MTU defined technical specifications. It is the customer's sole responsibility to ensure that the export/import, installation and use of the engine and/or system complies with the applicable emissions regulations in the country or region where the engine and/or system will be used.	
<b>2.2 Exhaust System</b>	1,
Unit-Mounted Silencer 5"	1,
• Silencer Model Number: CPJS-05X-90040066	
• Qty 1	
<b>2.3 FUEL SYSTEM</b>	1,



A Rolls-Royce  
solution


		valid for product no.
	Tank Includes Spill Fill Containment (5 Gallon capacity)	1,
	48 HR 800 Gallons Extended Sub Base Fuel Tank (with Rear Stub-Up)	1,
<b>2.4</b>	<b>Air Intake System</b>	1,
	Air Filter (Standard)	1,
	MTU Air Filter	1,
	• XG2112100001	
	• Qty 1	
<b>3</b>	<b>GENERATOR CONFIGURATION</b>	1,
<b>3.1</b>	<b>Generator Specification</b>	1,
	Generator Model Number: 431/6208	1,
<b>3.2</b>	<b>Generator accessories</b>	1,
	PMG with DVR 2400	1,
	• True RMS Sensing - One or Three Phase Connect. Senses 100 to 600 volts ±10% at 50/60 Hertz. Patented circuitry senses true RMS voltage rather than average for superior load regulation.	
<b>4</b>	<b>CONTROL PANEL CONFIGURATION</b>	1,
<b>4.1</b>	<b>Control panel</b>	1,
	Circuit Breaker Position 1:	1,
	Without Ground Fault	1,
	Modbus RTU	1,
	• ModBus RTU connects the MGC to Programmable Logic Controllers by means of communication transmission over serial lines (RS485).	
	Modem RS-232	1,
	• The MGC controller includes an external modem interface permitting an external modem to be connected to the controller via RS-232. A dial-out modem enables remote control, monitoring, and setting of the controller. When an alarm or pre-alarm condition occurs, the controller can dial up to four telephone numbers in sequence until an answer is received and the condition is annunciated.	
	○ Note: Only an external modem interface is provided. The external modem must be supplied by a third party	



A Rolls-Royce  
solution

valid for  
product no.


1,



**Top View**      **Right Side**      CB Position 1/CB Position 2  
**Left Side**      Controls/CB Position 3

\* For technical data refer to the circuit breaker enclosure data sheets located on the Business Portal

1,



**Top View**      **Right Side**      CB Position 1/CB Position 2  
**Left Side**      Controls/CB Position 3

\* For technical data refer to the circuit breaker enclosure data sheets located on the Business Portal

High Fuel Level Pre-Alarm

1,

Critical Low Fuel Level Alarm

1,

Contact Expansion Module (CEM)

1,

- The CEM is a remote device that provides additional MGC contact inputs and outputs giving the user flexibility to use the same model MGC generator set controller for simple or more complicated applications that require contact functionality or duplication of contacts for remote annunciation.

Modbus RTU

1,

- ModBus RTU connects the MGC to Programmable Logic Controllers by means of communication transmission over serial lines (RS485).

MGC- 2000 Series

1,

- MTU Onsite Energy's Digital Genset Controller MGC-2000 series is a highly advanced integrated generator set control system. The MGC-2000 series is perfectly focused, combining rugged construction and microprocessor technology to offer a product that will hold



A Rolls-Royce  
solution

valid for  
product no.

up to almost any environment and flexible enough to meet your application's needs. This device provides generator set control, transfer switch control, metering, protection, and programmable logic in a simple, easy-to-use, reliable, rugged, and cost effective package.

No Parallel Operation

1,

## 5 SERVICES AND AFTER SALES SUPPLY

### 5.1 Warranty

General Terms and Conditions of Sale, Warranty and After Sales Supply

Our offer is based on the attached General Terms and Conditions of Sale for MTU Products (Rev. V-601-1803 MUS & MOE) and the Warranty will be the attached Standard Two (2) Year / 3,000 Hour Basic Standby (3D), Prime (3B), and Data Center Continuous Power (DCCP) (3F) Limited Warranty (SYS-M-GEN-S-026).

## 6 MISCELLANEOUS

### 6.1 Painting

Paint Color: RAL 7001 Grey

1,

1,

### 6.2 Documentation

English

1 Flash Drive

1,

1,

English

French

Spanish

1,

1,

1,

1,

### 6.3 Additional Options

Mechanical Drawing: Genset Dimensional HSD  
• XZG2100100038

1,

1,

Mechanical Drawing: Genset Dimensional HSG  
• XZG2100100040

1,

Mechanical Drawing: Fuel Tanks  
• XZG2100100047

1,

Electrical Drawing: Engine  
• XZG21K0000003

1,

Electrical Drawing: Generator  
• XZG21K0000010

1,



A Rolls-Royce  
solution

valid for  
product no.

Electrical Drawing: Breaker Options  
• XZG21K0000002

1,

Electrical Drawing: Control Panel  
• XZG2100100055

1,

Electrical Drawing: Options Sheet  
• XZG21K0000009

1,

## 7 FUNCTIONAL TESTING

1,

### 7.1 Acceptance Testing

1,

Standard Commercial Test

1,

## 8 SHIPPING CONDITIONS

1,

### 8.1 Shipment

1,

Ship unit with fluids installed

1,

Genset Unit is enclosed in a Shipping Bag

1,